## **Derivation of the Wave Equation**

In these notes we apply Newton's law to an elastic string, concluding that small amplitude transverse vibrations of the string obey the wave equation. Consider a tiny element of the string.



The basic notation is

u(x,t) = vertical displacement of the string from the x axis at position x and time t

 $\theta(x,t)$  = angle between the string and a horizontal line at position x and time t

T(x,t) =tension in the string at position x and time t

 $\rho(x) =$ mass density of the string at position x

The forces acting on the tiny element of string are

- (a) tension pulling to the right, which has magnitude  $T(x + \Delta x, t)$  and acts at an angle  $\theta(x + \Delta x, t)$  above horizontal
- (b) tension pulling to the left, which has magnitude T(x,t) and acts at an angle  $\theta(x,t)$  below horizontal and, possibly,
- (c) various external forces, like gravity. We shall assume that all of the external forces act vertically and we shall denote by  $F(x,t)\Delta x$  the net magnitude of the external force acting on the element of string.

The mass of the element of string is essentially  $\rho(x)\sqrt{\Delta x^2 + \Delta u^2}$  so the vertical component of Newton's law says that

$$\rho(x)\sqrt{\Delta x^2 + \Delta u^2} \frac{\partial^2 u}{\partial t^2}(x,t) = T(x + \Delta x,t)\sin\theta(x + \Delta x,t) - T(x,t)\sin\theta(x,t) + F(x,t)\Delta x$$

Dividing by  $\Delta x$  and taking the limit as  $\Delta x \to 0$  gives

$$\rho(x)\sqrt{1 + \left(\frac{\partial u}{\partial x}\right)^2 \frac{\partial^2 u}{\partial t^2}(x,t)} = \frac{\partial}{\partial x} \left[T(x,t)\sin\theta(x,t)\right] + F(x,t)$$

$$= \frac{\partial T}{\partial x}(x,t)\sin\theta(x,t) + T(x,t)\cos\theta(x,t)\frac{\partial\theta}{\partial x}(x,t) + F(x,t)$$
(1)

(c) Joel Feldman. 2002. All rights reserved.

We can dispose of all the  $\theta$ 's by observing from the figure that

$$\tan \theta(x,t) = \lim_{\Delta x \to 0} \frac{\Delta u}{\Delta x} = \frac{\partial u}{\partial x}(x,t)$$

which implies, using the figure on the right below, that

$$\sin \theta(x,t) = \frac{\frac{\partial u}{\partial x}(x,t)}{\sqrt{1 + \left(\frac{\partial u}{\partial x}(x,t)\right)^2}} \quad \cos \theta(x,t) = \frac{1}{\sqrt{1 + \left(\frac{\partial u}{\partial x}(x,t)\right)^2}} \quad \underbrace{\sqrt{1 + \tan^2 \theta}}_{1} \tan \theta$$
$$\theta(x,t) = \tan^{-1} \frac{\partial u}{\partial x}(x,t) \quad \frac{\partial \theta}{\partial x}(x,t) = \frac{\frac{\partial^2 u}{\partial x^2}(x,t)}{1 + \left(\frac{\partial u}{\partial x}(x,t)\right)^2}$$

Substituting these formulae into (1) give a horrendous mess. However, we can get considerable simplification by looking only at small vibrations. By a small vibration, we mean that  $|\theta(x,t)| \ll 1$  for all x and t. This implies that  $|\tan \theta(x,t)| \ll 1$ , hence that  $\left|\frac{\partial u}{\partial x}(x,t)\right| \ll 1$  and hence that

$$\sqrt{1 + \left(\frac{\partial u}{\partial x}\right)^2} \approx 1 \qquad \sin \theta(x, t) \approx \frac{\partial u}{\partial x}(x, t) \qquad \cos \theta(x, t) \approx 1 \qquad \frac{\partial \theta}{\partial x}(x, t) \approx \frac{\partial^2 u}{\partial x^2}(x, t) \quad (2)$$

Substituting these into equation (1) give

$$\rho(x)\frac{\partial^2 u}{\partial t^2}(x,t) = \frac{\partial T}{\partial x}(x,t)\frac{\partial u}{\partial x}(x,t) + T(x,t)\frac{\partial^2 u}{\partial x^2}(x,t) + F(x,t)$$
(3)

which is indeed relatively simple, but still exhibits a problem. This is one equation in the two unknowns u and T.

Fortunately there is a second equation lurking in the background, that we haven't used. Namely, the horizontal component of Newton's law of motion. As a second simplification, we assume that there are only transverse vibrations. Our tiny string element moves only vertically. Then the net horizontal force on it must be zero. That is,

$$T(x + \Delta x, t) \cos \theta(x + \Delta x, t) - T(x, t) \cos \theta(x, t) = 0$$

Dividing by  $\Delta x$  and taking the limit as  $\Delta x$  tends to zero gives

$$\frac{\partial}{\partial x} \left[ T(x,t) \cos \theta(x,t) \right] = 0$$

For small amplitude vibrations,  $\cos \theta$  is very close to one and  $\frac{\partial T}{\partial x}(x,t)$  is very close to zero. In other words T is a function of t only, which is determined by how hard you are pulling on the ends of the string at time t. So for small, transverse vibrations, (3) simplifies further to

$$\rho(x)\frac{\partial^2 u}{\partial t^2}(x,t) = T(t)\frac{\partial^2 u}{\partial x^2}(x,t) + F(x,t)$$
(4)

In the event that the string density  $\rho$  is a constant, independent of x, the string tension T(t) is a constant independent of t (in other words you are not continually playing with the tuning pegs) and there are no external forces F we end up with

$$\frac{\partial^2 u}{\partial t^2}(x,t) = c^2 \frac{\partial^2 u}{\partial x^2}(x,t)$$

where

$$c = \sqrt{\frac{T}{\rho}}$$